



WELLIX HYBRID 5W-30



FULLY SYNTHETIC HIGH-PERFORMANCE ENGINE OILS

DESCRIPTION AND APPLICATION

It is a synthetic engine oil specifically designed for next-generation Hybrid Electric Vehicles (H.E.V) and Plug-in Hybrid Electric Vehicles (P.H.E.V), as well as new gasoline engines, whether turbocharged or naturally aspirated, with direct or indirect injection systems. With its formulation that provides wear protection, keeps the engine clean, offers high shear stability, and ensures optimum thermal stability, it delivers excellent protection for your engine. It facilitates quick lubrication in vehicles with start-stop technology. It provides protection against low-speed pre-ignition (LSPI) at low speeds. Its excellent fluidity in cold weather ensures quick lubrication of engine parts during initial start-up, thereby protecting the engine from wear and reducing both oil and fuel consumption.

FEATURES AND BENEFITS

- Thanks to its superior thermal and oxidation stability, it maintains performance until the next oil change.
- It ensures smooth engine starts and instant lubrication after cold starts, protecting the engine from wear.
- It demonstrates excellent performance at both high and low temperatures.
- It offers exceptional engine cleanliness and wear resistance.
- Its low volatility reduces oil consumption.
- It provides fuel savings and reduces pollutant emissions.

PERFORMANCE

Meets the performance specifications of API: SN / CF , ACEA C3, ILSAC GF-6B GM Dexos1 Gen3.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with the skin or eyes, should not be ingested, and its fumes should not be inhaled. If contact occurs with the skin or eyes, it should be washed with plenty of soapy water, and medical assistance should be sought if necessary. If swallowed, do not induce vomiting, and emergency medical help should be sought. In case of inhaling fumes, breathe in fresh air and seek medical help if needed. Used Lubran motor oils should not be discarded in the trash, sewer, or any other receptacles and should be collected in appropriate waste oil containers and delivered to authorized recycling centers in accordance with current regulations. Do not mix any petroleum product or chemical with the oil. It should not be burned in stoves or boilers. It must be stored in places inaccessible to children. Empty containers should not be thrown in the trash or disposed of in the environment, and they should be handed over to licensed recycling organizations. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packaging should not be exposed to long-term direct sunlight. Containers should be kept away from water and should not come into contact with it. The oils must not be exposed to dust, and the storage environment should be clean. The temperature should not exceed 40°C. It is the user's responsibility to follow the relevant laws and regulations. Lubran is not responsible for any damages or losses that may result from misuse or use outside the intended purpose of the product.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	WELLIX HYBRID 5W-30
Density, g/cm ³ 15°C	ASTM D 4052	0,850
Kin. Viscosity , cSt, 100°C	ASTM D 445	9,3-12,5
Viscosity Index min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-36
Flash Point, °C, min.	ASTM D 92	220

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE