



WELLIX 5W-20



FULLY SYNTHETIC HIGH-PERFORMANCE ENGINE OILS

DESCRIPTION AND APPLICATION

LUBRAN FULLY SYNTHETIC WELLIX 5W-20 is a fully synthetic engine oil formulated with state-of-the-art additives for modern passenger vehicle engines, providing fuel economy. It can be safely used in gasoline engines requiring API SN and ACEA A1/B1 performance level oils in all seasons.

FEATURES AND BENEFITS

- Thanks to its advanced additive technology, it keeps the engine clean, reduces friction, and ensures optimal energy efficiency and extended service life.
- Its synthetic formulation provides exceptional protection and fuel savings.
- It extends engine life and lubrication intervals while improving fuel economy.
- It delivers full performance under all climate and road conditions.
- With excellent low-temperature properties, it eliminates all potential wear during cold starts.

PERFORMANCE

Meets the performance specifications of API SN/SN(RC), ACEA A1/B1, ILSAC GF-5, FORD WSS-M2C948-A, FORD WSS-M2C948-B, and Fiat 9.55535-CR1, Gm dexos 1 GEN 2 .

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Lubran motor oil should not come into contact with the skin or eyes, should not be ingested, and its fumes should not be inhaled. If contact occurs with the skin or eyes, it should be washed with plenty of soapy water, and medical assistance should be sought if necessary. If swallowed, do not induce vomiting, and emergency medical help should be sought. In case of inhaling fumes, breathe in fresh air and seek medical help if needed. Used Lubran motor oils should not be discarded in the trash, sewer, or any other receptacles and should be collected in appropriate waste oil containers and delivered to authorized recycling centers in accordance with current regulations. Do not mix any petroleum product or chemical with the oil. It should not be burned in stoves or boilers. It must be stored in places inaccessible to children. Empty containers should not be thrown in the trash or disposed of in the environment, and they should be handed over to licensed recycling organizations. For more detailed information, refer to the "Material Safety Data Sheet."

STORAGE CONDITIONS

Lubran motor oil packaging should not be exposed to long-term direct sunlight. Containers should be kept away from water and should not come into contact with it. The oils must not be exposed to dust, and the storage environment should be clean. The temperature should not exceed 40°C. It is the user's responsibility to follow the relevant laws and regulations. Lubran is not responsible for any damages or losses that may result from misuse or use outside the intended purpose of the product.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	WELLIX 5W-20
Density, g/cm ³ 15°C	ASTM D 4052	0,850
Kin. Viscosity , cSt, 100°C	ASTM D 445	6,9-9,3
Viscosity Index min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min.	ASTM D 92	220

PACKAGING TYPES



KÜNDE PETROL ÜRÜNLERİ SAN. VE TİC. LTD. ŞTİ.
OSB MAH, 19. Sk. NO:14, 35170 Kemalpaşa / İzmir / TÜRKİYE